



**Speed**  
6" (152mm) / sec.



**Resolution**  
203 DPI.




**Flash Memory**  
8 MB



**The only one.**

**Temperature**  
Auto adjustable.

**Print anytime and anywhere!**



## FEATURES

- 8MB flash memory, 8MB SDRAM.
- 152 mm(6")/s printing speed.
- Support single sheet printing.
- It can intelligently adjust the temperature during continuous printing.

## SPECIFICATIONS

Code	TLP-2054N-BU
Resolution	203dpi
Printing method	Direct thermal
Print speed	152mm (6") /s max.
Max. print width	108mm (4.25")
Max. print length	1778mm (70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	26mm ~ 116mm
Media thickness	0.06mm ~ 0.20 mm
Label length	10 ~ 1778mm
Gap height	<2mm
Black mark height	<2mm
Processor	32-bit CPU
Memory	8MB flash memory / 8MB SDRAM
Interface	Standard: USB, Optional: WiFi, Bluetooth, Cloud WiFi
Sensors	Gap sensor, cover opening sensor, black mark sensor and paper exit sensor
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D barcode	Code 39, 93, 128UCC, 128, subsets A,B,C, codabar, interleaved 2 of 5, EAN8, EAN13, EAN128, UPC-A, UPC-E, EAN & UPC2(5) digits add-on, MSI, Plessey, Postnet, China Post
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, ZPL, EPL, DPL
Driver	Windows / Linux / Mac
SDK	Windows / Android / iOS
Input	Ac 100-240V, 50-60Hz
Output	DC 24V, 2.5A
Factory options	1. WiFi, 2. Bluetooth, 3. Cloud WiFi
Dealer options	External paper roll holder
Operation environment	5 ~ 40°C (41 ~ 104°F), Humidity 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C (-40 ~ 140°F), Humidity 10 ~ 90% non-condensing
Dimension	185mm(w)x85mm(H)x85mm(D)
Weight	722g
Print head life	30Km

*\*The specifications and external design are subject to change without notice for further improvement.*